



**CONSTRUCTION:** Lead-Free Brass

**MOUNT TYPE:** Floor Standing

**CARTRIDGE:** Ceramic Cartridge

**INLET & OUTLET CONNECTIONS:** ½" BSP

**WORKING PRESSURES:** 0.50 – 10.0 Bar

**OPERATING TEMPERATURE:** 5°C – 80°C

**SUPPLY:** Suitable for all plumbing Systems

**OPERATION:** Single lever flow & temperature control

- Made from brass to preserve water quality
- Citec ceramic cartridges for smooth operation
- Neoperl constant flow aerator
- Available in assorted finishes
- Solid brass lever

**OPEN OUTLET FLOW (Bar – l/min)**

15 Year Guarantee

Bar	1.0	1.5	2.0	2.5	3.0	3.5	4.0
Spout	5.8	6.8	7.7	8.6	9.5	10.4	11.3
Handheld Shower	5.0	5.7	6.4	7.1	7.8	8.2	8.5

Please Note: Flow rate will be dictated by installation configurations. Please ensure to check the appropriate flow restrictor information if applicable. Please refer to the website for fully warranty details.

**CERTIFICATION:**

- WRAS APPROVED:
- UPC
- CE
- WATERPARK

FURTHER DETAILS & DIMENSIONS CAN BE FOUND AT [WWW.LUSSOSTONE.COM](http://WWW.LUSSOSTONE.COM) IN THE FEATURE SECTION AND DOWNLOADS TAB OF EACH PRODUCT PAGE.

TEL: 0203 370 4057

EMAIL: [SALES@LUSSO.COM](mailto:SALES@LUSSO.COM)

[WWW.LUSSO.COM](http://WWW.LUSSO.COM)

THE INFORMATION ON THIS SPECIFICATION DOCUMENT WAS CORRECT AT THE DATE OF ISSUE. SOME VARIATION MAY OCCUR DUE TO MANUFACTURING TOLERANCES AND SITE-SPECIFIC CONDITIONS.